

Appl. No. 09/766,616  
Amdt. Dated May 25, 2004  
Reply to Office action of February 26, 2004  
Attorney Docket No. P13207-US2  
EUS/JP/04-2004

This listing of claims replaces all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Previously Presented) A method for adjusting the clock of a base transceiver station comprising the steps of:  
relating the base transceiver station's current time to a common time reference;  
providing the base transceiver station with an offset based on the relation;  
determining global positioning satellite (GPS) time;  
providing assistance data for decoding the chip sequence of a GPS signal; and  
comparing the GPS time to the time of the base transceiver station's clock,  
wherein the base transceiver station's clock is adjusted based upon the offset and the comparison.
2. (Original) The method of claim 1, further comprising the steps of:  
measuring the time of base transceiver stations surrounding the base transceiver station; and  
measuring the time of the base transceiver station's clock.  
*b*
3. (Original) The method of claim 2, further comprising the steps of:  
providing a frame number and approximate control channel position of base transceiver stations surrounding the base transceiver station, wherein the time of base transceiver stations surrounding the base transceiver station and the time of the base transceiver station's clock are measured using the frame number and approximate control channel position.
4. (Original) The method of claim 3, wherein the frame number is transmitted in a broadcast control channel and the approximate control channel position is a position of a shared control channel.

Appl. No. 09/766,616  
Amdt. Dated May 25, 2004  
Reply to Office action of February 26, 2004  
Attorney Docket No. P13207-US2  
EUS/J/P/04-2004

5. (Original) The method of claim 2, wherein the base transceiver station is provided with information from a location measurement unit, wherein the base transceiver station's clock is adjusted based upon the information from the location measurement unit.

6. (Original) The method of claim 5, wherein the location measurement unit is associated with the base transceiver station.

7. (Original) The method of claim 5, wherein the location measurement unit is associated with another base transceiver station, wherein the another base transceiver station is within radio range of the base transceiver station.

*B1  
Cont.*  
8. (Original) The method of claim 5, wherein the information contains an indication of the accuracy of the clock of a base transceiver station used for generating the information.

9. (Original) The method of claim 1, wherein if the common time reference is not available, another base transceiver station's clock is used as the common time reference.

10. (Original) The method of claim 9, wherein the another base transceiver station's clock is used for synchronization of equipment co-sited with the base transceiver station.

11-12. (Cancelled)

13. (Previously Presented) The method of claim 1, wherein the GPS time is determined by examining messages of a GPS signal.

Appl. No. 09/766,616  
Amdt. Dated May 25, 2004  
Reply to Office action of February 26, 2004  
Attorney Docket No. P13207-US2  
EUS/J/P/04-2004

14. (Original) The method of claim 1, wherein the offset is provided by a serving mobile location center.

15. (Previously Presented) A system comprising:

means for relating the base transceiver station's current time to a common time reference;

means for providing the base transceiver station with an offset based on the relation;

means for determining global positioning satellite (GPS) time;

means for providing assistance data for decoding the chip sequence of a GPS signal; and

means for comparing the GPS time to the time of the base transceiver station's clock, wherein the base transceiver station's clock is adjusted based upon the offset and the comparison.

*b1*  
*Cont.*

16. (Original) The system of claim 15, further comprising:

means for measuring the time of base transceiver stations surrounding the base transceiver station; and

means for measuring the time of the base transceiver station's clock.

17. (Original) The system of claim 16, further comprising:

means for providing a frame number and approximate control channel position of base transceiver stations surrounding the base transceiver station, wherein the time of base transceiver stations surrounding the base transceiver station and the time of the base transceiver station's clock are measured using the frame number and approximate control channel position.

18. (Original) The system of claim 17, wherein the frame number is transmitted in a broadcast control channel and the approximate control channel position is a position of a shared control channel.

Appl. No. 09/766,616  
Amtd. Dated May 25, 2004  
Reply to Office action of February 26, 2004  
Attorney Docket No. P13207-US2  
EUS/J/P/04-2004

19. (Original) The system of claim 16, wherein the base transceiver station is provided with information from a location measurement unit, wherein the base transceiver station's clock is adjusted based upon the information from the location measurement unit.

20. (Original) The system of claim 19, wherein the location measurement unit is associated with the base transceiver station.

21. (Original) The system of claim 19, wherein the location measurement unit is associated with another base transceiver station, wherein the another base transceiver station is within radio range of the base transceiver station.

*B1*  
*cont*  
22. (Original) The system of claim 19, wherein the information contains an indication of the accuracy of the clock of a base transceiver station used for generating the information.

23. (Original) The system of claim 15, wherein if the common time reference is not available, another base transceiver station's clock is used as the common time reference.

24. (Original) The system of claim 23, wherein the another base transceiver station's clock is used for synchronization of equipment co-sited with the base transceiver station.

25-26. (Cancelled)

27. (Previously Presented) The system of claim 15, wherein the GPS time is determined by examining messages of a GPS signal.

Appl. No. 09/766,616  
Amdt. Dated May 25, 2004  
Reply to Office action of February 26, 2004  
Attorney Docket No. P13207-US2  
EUS/JP/04-2004

28. (Original) The system of claim 15, wherein the offset is provided by a serving mobile location center.

*B1*  
*Cancelled.*  
29-36. (Cancelled).

\* \* \*